

Thread tapping machine

avoid scrap and tapping tool breakage



jobtap II-G8

Thread capacity

(DIN13, sheet.34 / 1,2 x D)

Torque range

Spindle speed range

Thread depth / stroke max

Column with hand crank

Base plate / 2xT-Nut / PG6

Distance spindle to column.

Tapered shaft / spindle

Width / depth / height

Power supply requirements

Compliance to safety regulation

Finish

Operation

Error messages

LCD Display and Menu Driven

Software - includes

M2.5-M8 (#3-5/16) X5CrNi189 (Stainless Steel)

M2.5-M10 (#3-3/8) 9sMn28 (Carbon Steel)

M2.5-M12 (#3-7/16) AlCuMgPb (Al Alloys)

50-700Ncm (470Ncm max above 2060RPM)

300 - 3000 RPM

75 / 80 mm (2.95 / 3.15 Inch)

750 mm (29.5 Inch)

288 x 475 x 50 mm/ M12x14 DIN650/ G1/4

(11.34" x 18.7" x 1.97") / for 1/2" T-slot bolts

400 mm (15.5 Inch)

B12

320 / 470 / 1290 mm (12.6 / 18.5 / 50.8 Inch)

230 volt, 50/60Hz, 1 phase, 2900 Watt

- CE, EMV conformity

- RAL 7016 dark gray

- menu driven

- Audible alarm and display

- Language selector

- Torque display and setting for min/max

- Right or Left hand threads

- Fast, normal, and slow reverse speeds

- Lubrication pulse control

- Variable chip clearance function

- Automatic start, position and depth control

- User data storage for 40 part parameters

- Single and total thread counter

- Cutting force start sensor (with ZAP system)

- mm/Inch and metric/UNF-UNC selection



jobtap II-G8

Insert holder SWS1

Quick change holder, without inserts

Price

Quick-Change tap adapters for above SWS1 holder

Standard package

Additional adapters

Reduced Shank

Precision compensation

Price

Other systems

Type EM 01

No. 0-6, 8, 10, 1/4, 3/8"


12, 1/16 NPT, 5/16"

7/16, 1/2, 9/16, 1/8 NPT, 5/8"

0.05 mm, only with inserts from microtap

each size

on request



ZAP-tap

air pressure

air connection

pneumatic **Z-Axis** spindle feeding system
integrated machine controlled feeding system
for thread tapping with footswitch

4-6 bar / 60-90 PSI

4/6 mm



Price

jobtap-G8

microtap USA, Inc., 2146 Avon Industrial Drive, Rochester Hills, Michigan 48309, USA, Telephone (248)-852-8277, Fax: (248)-852-5298

Email: sales@threadtapping.com

Internet: <http://www.threadtapping.com>

05/11/09