



Seghe a tazza HSS-G

Unità d'imballo: in confezione di plastica

Acciaio (N/mm ²) < 900					
Acciaio (N/mm ²) < 1100					
Acciaio (N/mm ²) < 1300					
Acciaio inossidabile					
Alluminio					
Ottone					
Bronzo					
Materie plastiche					
Ghisa					
Lega di titanio					



Ø1 mm	Ø pollici	PG	Misure pollici	Ø2 mm	HSS		
12,0	15/32			8,0	128 012	1	
13,0				8,0	128 013	1	
14,0	9/16			8,0	128 014	1	
15,0				10,0	128 015	1	
16,0	5/8	PG 9		10,0	128 016	1	
17,0				10,0	128 017	1	
18,0				10,0	128 018	1	
19,0	3/4		3/8	10,0	128 019	1	
20,0				10,0	128 020	1	
21,0				10,0	128 021	1	
22,0			1/2	10,0	128 022	1	
23,0				10,0	128 023	1	
24,0	15/16			10,0	128 024	1	
25,0				10,0	128 025	1	
26,0				10,0	128 026	1	
27,0	1 1/16			10,0	128 027	1	
28,0	1 3/32			10,0	128 028	1	
29,0			3/4	10,0	128 029	1	
30,0	1 3/16			10,0	128 030	1	
31,0	1 7/32			10,0	128 031	1	
32,0	1 1/4			10,0	128 032	1	
33,0				10,0	128 033	1	
34,0				10,0	128 034	1	

Ø1 mm	Ø pollici	PG	Misure pollici	Ø2 mm	HSS		
35,0	1 3/8		1	10,0	128 035	1	
36,0				10,0	128 036	1	
37,0	1 7/16	PG 29		10,0	128 037	1	
38,0	1 1/2			10,0	128 038	1	
39,0				10,0	128 039	1	
40,0	1 9/16			10,0	128 040	1	
41,0	1 5/8			10,0	128 041	1	
42,0				10,0	128 042	1	
43,0	1 11/16			10,0	128 043	1	
44,0	1 3/4		1 1/4	10,0	128 044	1	
45,0				10,0	128 045	1	
46,0				10,0	128 046	1	
47,0	1 7/8	PG 36		10,0	128 047	1	
48,0				10,0	128 048	1	
49,0				10,0	128 049	1	
50,0	1 31/32			10,0	128 050	1	
55,0				12,0	128 055	1	
60,0	2 3/8	PG 48		12,0	128 060	1	
65,0				12,0	128 065	1	
70,0	2 3/4			12,0	128 070	1	
75,0				12,0	128 075	1	
80,0				12,0	128 080	1	



Accessorio

Unità d'imballo: in confezione di plastica



	Per seghe da traforo Ø mm	Gambo	Trapano a cavalletto magnetico	HSS		
Portasupporto con punta guida M 10 x 1,25 mm	12,0 - 14,0	Ø 8,0 mm	RS10	128 211	1	
Portasupporto con punta guida M 12 x 1,25 mm	15,0 - 34,0	Ø 10,0 mm	RS10	128 212	1	
Portasupporto con punta guida M 14 x 1,50 mm	35,0 - 50,0	Ø 10,0 mm	RS20 - RS40e	128 213	1	
Portasupporto con punta guida M 16 x 1,50 mm	51,0 - 100,0	Ø 12,0 mm	RS20 - RS40e	128 214	1	
Perno di guida Ø 6,0 x 52,0 mm	12,0 - 100,0	-	-	128 215	1	
Molla di espulsione	Ø > 20,0	-	-	128 216	1	